

Low-VOC* Colorants

Color Solutions

Colortrend® 805

General Information

Colortrend 805 colorants are uniquely formulated, low-VOC and used for point-of-sale tinting of Architectural paints and coatings. They have excellent rheological properties, provide minimal impact on coating performance, and are very low-odor.



Applications

Colortrend 805 colorants are universal and can be used in a wide range of Decorative waterborne and solventborne coating systems.

Key Benefits

- Compliance with current and future VOC regulations.
- Utilizes the newest technologies, delivering improved performance.
- Assures high compatibility in a wide range of base formula compositions.
- Superior rheology delivers outstanding stability with minimal settling.



- Improved scrub resistance compared to other standard competitive colorants.
- Colorant consistency ensures highly dependable and reproducible tinting accuracy.

Other Uses

Colortrend 805 Colorants can be used in many other types of products requiring coloring including: latex adhesives, caulks and sealants, grout, coated papers, leather coatings, and rubber latex products.

Product Code	Description	Can Code	CI	Typical Lbs/Gal	Specific Gravity	Composition by Weight			Composition by Volume			VOC g/L
						Pigment Solids	Vehicle	Volatiles	Pigment Solids	Vehicle	Volatiles	
805-0018	Titanium White	KX	PW 6	16.1	1.94	65.2	14.2	20.6	36.4	29	34.6	4
805-0422	Magenta	V	PR 122	11.5	1.38	45.7	11.9	42.4	28.7	15.9	55.4	4
805-0426	Magenta	VL	PR 122	9.6	1.15	34.1	15	50.9	21.4	20	58.6	4
805-0755	Organic Red	R	PR 254 blend	9.6	1.15	38.3	20.1	41.6	23	22.6	54.4	2
805-0836	Organic Red	RL	PR 188	10.9	1.31	41.9	17.1	41	23.4	23	53.6	8
805-1045	Red Oxide	F	PR 101	17.0	2.04	61.9	14.3	23.8	30	30	40	3
805-1577	Brown Oxide	I	Blend	14.3	1.72	53.7	19	27.3	30	32	38	3
805-1810	Yellow Oxide	C	PY 42	15.3	1.84	60.8	14	25.2	29.1	27.3	43.6	5
805-2007	Raw Umber	L	PBr 7	12.0	1.44	41.3	20.6	38.1	23.1	23.8	53.1	5
805-2040	Medium Yellow	T	Blend	10.5	1.26	44.9	18.4	36.7	28.2	23.9	47.9	6
805-2504	Perma Cal Yellow	AX	Blend	11.1	1.33	46.9	17.2	35.9	29.5	23.6	46.9	8
805-2860	High Hide Yellow	Y	PY184	17.8	2.13	63.4	19.4	17.2	35.9	30.1	34	4
805-5511	Phthalo Green	D	PG 7	11.0	1.32	36	16	48	22.6	14.7	62.7	7
805-7214	Phthalo Blue	E	PB 15:2	10.8	1.30	33.6	23.1	43.3	21.1	22.3	56.6	7
805-8895	Carbazole Violet	J	PV 23	11.4	1.37	44	15	41	26.4	20	53.6	7
805-9907	Lamp Black	B	PBk 7	11.4	1.37	41.7	16.7	41.6	26.7	19.5	53.8	3

*VOC per ASTM D6886, Colorants meet SCAQMD Rule 1113 <50 g/L

The information and recommendations contained herein are based on data we believe to be reliable and does not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. The data herein is determined using Vibrantz's standard test methods. Hazard and safety information with respect to this product is available in the applicable SDS. Vibrantz will not be liable under any circumstance for consequential or incidental damages, including but not limited to, lost profits resulting from the use of our products